

R 5

Rotary Vane Vacuum Pumps RA 0400–0630 C



› **Reliable:**

robust construction, reliable operation, highly resilient carbon fibre vanes, proven performance, over 3 million pumps in operation

› **High Performance:**

high pumping speed and low ultimate pressure, designed for continuous operation

› **Flexible:**

application-oriented, various design options available, easy adaption to individual customer requirements and processes

› **Low Operating Costs:**

energy-efficient, optimum cost-benefit ratio

› **Easy Servicing:**

easy service routine

The R 5 RA 0400–0630 C belong to the Busch product family of proven R 5 rotary vane vacuum pumps. They have been specially designed for use in a wide range of applications, such as food packaging, pneumatic conveying, vacuum cooling, vapor recovery and many more. They are perfectly suited for vacuum systems with large volume flows.

Robustness and reliability of operation are the outstanding qualities of R 5 rotary vane vacuum pumps. These are just some of the reasons why proven Busch rotary vane technology has long established itself as the industry standard. Over 3 million R 5 rotary vane vacuum pumps are in operation worldwide in industry every day.

Rotary vane technology has been continuously developed and optimized by Busch in the course of over 50 years, always with a strong focus on economy and reliability of operation.

High efficiency is the benefit of this continual development.

R 5 rotary vane vacuum pumps are characterized by high pumping speeds even in low pressure ranges and therefore rapid evacuation times. They feature highly durable Busch carbon fibre composite vanes as standard, ensuring optimum performance together with long service life. The specially designed exhaust filters provide excellent oil separation.

Maintenance can easily be carried out by the operator. Apart from changing oil and filters at regular service intervals, no further maintenance is required.

R 5 rotary vane vacuum pumps stand for advanced and energy-efficient vacuum generation in a wide variety of applications in industry throughout the world. You can always rely on the R 5 – whether used intermittently or around the clock.

**R 5 – proven and reliable.
Over 3 million pumps
in operation worldwide.**



R 5

Rotary Vane Vacuum Pumps RA 0400–0630 C




Technical specifications

Rotary vane technology is synonymous with a robust, functional construction. R 5 rotary vane vacuum pumps are characterized by an optimum design and perfectly synchronized components and materials. The constantly high vacuum level in continuous operation is ensured by recirculating oil lubrication and state-of-the-art precision manufacturing. A sophisticated oil separator ensures efficient use of oil. When fitted with a gas-ballast valve (optional), even large quantities of vapor can be extracted. A non-return valve in the inlet flange prevents the pumped medium from flowing back into the vacuum process after the vacuum pump is switched off. The R 5 RA 0400–0630 C are driven by a directly flange-mounted standard electric motor, with an efficiency class of IE3.

Accessories / Technical options


- IEC (IE3) and NEMA motors
- Multi-voltage, multi-frequency motors (IE3) for variable speed drive
- Single or double gas-ballast valve, manual or solenoid operation
- Various inlet filters
- Various temperature and pressure gauges
- Starter units
- Oil mist separator
- Energy recuperation kit with heat exchanger
- Vacuum pump oils for all applications

R 5 RA 0400–0630 C



Pumping speed

Air at 70 °F. Tolerance: ± 10%



Technical data		R 5 RA 0400 C	R 5 RA 0502 C	R 5 RA 0630 C
Max. pumping speed	ACFM	305	375	455
Ultimate pressure	Torr	0.075	0.075	0.075
Nominal motor rating	HP	15	20	25
Power consumption at 75 Torr	HP	13.4	16.0	20.0
Power consumption at ultimate pressure	HP	7.5	8.5	10.7
Nominal motor speed	RPM	1150	1150	1150
Sound level (ISO 2151)	dB(A)	79	79	79
Oil capacity	Qts.	14	16	16
Approximate weight	Lbs.	1084	1285	1527
Dimensions (L x W x H)	inches	54 1/2 x 40 x 28 1/2	65 x 40 x 28 1/2	69 1/4 x 41 1/2 x 28 1/2
Gas inlet	NPT	3"	3"	3"

All performance data is based on ambient conditions of 14.7 PSIA and 70 °F, and has a tolerance of ± 10%.

Busch LLC

516 Viking Drive | Virginia Beach, VA 23452 | Phone 757-463-7800 | info@buschusa.com | www.buschusa.com

Argentina Australia Austria Bangladesh Belgium Brazil Canada Chile China Colombia Czech Republic Denmark Finland France Germany Hungary India Ireland Israel Italy Japan Korea Malaysia Mexico Netherlands New Zealand Norway Peru Poland Portugal Romania Russia Singapore South Africa Spain Sweden Switzerland Taiwan Thailand Turkey United Arab Emirates United Kingdom USA

Technical data is subject to change. Created in Germany. MG PL R5RA04000630C USenus 04/2018 8Aa